

Floorstanding cistern, two-part Universal for floorstanding WC pan  
 82966.0



**TECHNICAL DATA**

Order no.	82966.0
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.7
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 982 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	21,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN- connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN- connection, order no. 89902.5 Angle valve for water inlet Water inlet hose

Colours see colour table

**SPECIFICATION TEXT**

Floorstanding cistern, two-part Universal Kartell • LAUFEN,  
 sanitary ceramic  
 EN 14055  
 dimensions 400/410 x 140 x 980 mm  
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)  
 water inlet side left, side right, 3/8" brass  
 matching floorstanding WC pan rimless, order no. 82333.7  
 Special feature: water condensation insulation  
 Order no. 82966.0

**TECHNICAL DRAWINGS / S 1 : 20**

